Technical Data Sheet







FOCUS ON HIGH-QUALITY LIFESTYLE

LVT CLICK FLOORING

FIOOF MEIODY YOUR ONE STOP FLOOR EXPE

FOCUS ON HIGH-QUALITY LIFESTYLE Size:5mm/0.5mm(T)X180mm(W)X1220mm(L)				
8pcs/carton Gross Weight 17.36Kg Net Weight 16.86KG				
More Bayel E		 UV coating wear layer HD decor films Fiberglass Middle Layer Fiberglass Unilin lock Backing Layer 		ULTRA URABILITY
Description	Standard	Symbol	Requirements	Results
			Domestic-Heavy(Class 23) Wear Layer (Nominal): ≥0.30mm Thickness (Nominal): ≥1.5mm	Passes Requirements (Nominal)
Classification (Level of Use)	EN ISO 10582 EN ISO 10582		Commercial-Very Heavy(Class 33) Wear Layer (Nominal): ≥0.50mm Thickness (Nominal): ≥2.0mm	Passes Requirements (Nominal)
			Light Industrial-Heavy(Class 43) Wear Layer (Nominal): ≥0.70mm Thickness (Nominal): ≥2.0mm	Passes Requirements (Nominal)
Dimensional Stability	ISO 23999:2021	『 て ゴ し		X Direction: 0.00% Y Direction: 0.00%
Curling	ISO 23999:2021	N/A		X Direction: 0.0mm Y Direction: 0.0mm
Residual Indentation	ISO24343		≤0.1mm	0.07mm
Colour Fastness to Light	ISO 105-B02, Method 3		≥Grade 6	Grade 6
Reaction to Fire (and Smoke Production)	EN 13501-1	B _{fl} -s1	B fl - S1 Classification Critical Flux: ≥8.0kW/m Flame Spread: ≤150mm within 20s Smoke value as % x min: ≤750	B _{f1} -S1
Castor Chair	ISO 4918:2016		Load: 90kg Type of wheels: Type W Cycles: 25000	Pass
Slip Resistance	EN 16165:2021-12	° A TI- DS	Class Ds: Test result 6°≤ashod<10°	R9
Phthalate	EN14372	M	 (1) 1mg/kg = 1 ppm = 0.0001% (2) MDL = Method Detection Limit (3) ND = Not Detected (< MDL) (4) "-"=Not Regulated 	ND
Thermal Resistance	EN 12667			Pass
Abrasion/ wear Resistance	EN 660-2		2.0 <fv≤4.0< td=""><td>Group P</td></fv≤4.0<>	Group P

Contact us

Click the link and explore more!

Google

Social Media Platform

https://www.facebook.com/FLOORMELODY.SG

https://www.youtube.com/results?search_query=floormelody

https://www.instagram.com/floor_melody/

Welcome to visit FLOORMELODY !

FLOOR MELODY Flooring

WWW.FLOORMELODY.COM.SG

Tel: +65 6974 4128 Web: www.floormelody.com.sg Email: sales@floormelody.com.sg